

DNAKE 280M-S3

Instruction

The 280M-S3 provides multiple functions, including audio and video intercom, emergency call, security alarm and lift control, etc. It also supports communication via SIP 2.0 protocol with IP phone and IP-PBX. It allows constructor to make an easy configuration and installation.



Key Features

- Easy configuration
- 10.1-inch capacitive touch screen
- Powered by PoE or power adapter (DC12V/2A)
- Support SIP 2.0 protocol, easy integration with other SIP devices
- Easy integration with elevator control system
- Support monitoring 8 IP cameras

Physical

- System: Linux
- RAM: 64 MB
- ROM: 128 MB
- Front Panel: Plastic
- Power Supply: PoE (802.3af) or DC 12V/2A
- Standby Power: 1.5 W
- Rated Power: 9 W
- Ethernet Ports: 1 x RJ45, 10/100 Mbps adaptive
- RS485: 1
- Power Output: 1 (12V/100mA)
- Doorbell Input: 8 (use any alarm input port)
- Alarm Input: 8
- Installation: Surface mounting
- Dimension: 270 x 168 x 15 mm
- Working Temperature: -10°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)



Datasheet

Display

- Display: 10.1-inch TFT LCD
- Screen: Capacitive touch screen
- Resolution: 1024 x 600

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: Built-in speaker

Video

- Video Codec: H.264

Networking

- Protocol: SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

