

Instruction

With an Android operating system, DNAKE B613-2 provides an integrated security solution. It enables user to open the door by facial recognition with liveness detection, IC card and PIN Code. It also makes an easy video call with indoor monitor and mobile APP, to achieve an convenient and secure life.

Key Features

- Open the door by face recognition (10,000 users)
- Liveness detection
- Open the door by IC card (100,000 users)
- Support SIP 2.0 protocol, easy integration with other SIP devices
- Easy integration with elevator control system
- 2MP camera with WDR mode

Physical

- System: Android
- RAM: 1 GB
- ROM: 8 GB
- Front Panel: Aluminum
- Button: Mechanical
- Power Supply: Powered by 2 wire distributor or DC 48V
- Standby Power: 8 W
- Rated Power: 28 W
- Camera: 2MP, CMOS, WDR
- IR Sensor: Support
- Wiegand Port: Support
- Door Entry: Face, IC/ID card, PIN code
- RS485 Port: 1
- Relay Out: 2
- Exit Button: 4
- Door Magnetic: 4
- IP Rating: IP65 (Seal up the cracks between door station and the wall with glass glue.)
- Installation: Flush Mounting
- Dimension: 380 x 158 x 55.7 mm
- Working Temperature:
 - 10°C to +55°C (default);
 - 40°C to +55°C (with heating film)
- Storage Temperature: -10°C to +60°C
- Working Humidity: 10% to 90% (non-condensing)

B613-2



Datasheet

Display

- Display: 4.3-inch TFT LCD
- Resolution: 480x272

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: Built-in speaker

Video

- Video Codec: H.264
- Video Resolution: up to 1080 x 1920
- Viewing angle: 96° (D)
- Max. Image Transfer Rate: 1080p – 25fps
- Light Compensation: LED white light

Networking

- Protocol: SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Package Features

- Package Content:
 - B613-2
(Power adapter not included)
 - Flush Mounting Box
 - Screwing Kit
 - Quick Start Guide
- Qty/CTN: 8 pcs
- N.W/PCS: 2.19 kg
- G.W/CTN: 21.1 kg
- Giftbox Size: 470 x 210 x 100 mm
- Carton Size: 480 x 410 x 435 mm

